

Category : Cars
Make : Opel
Model : Zafira A, T98 (1999 - 2005)
Type : Zafira 1.8-16V (1999 - 2000)
Remarks :

Engine X18XE1

Capacity: Capacity 4,25 litre
 Filter capacity 0,4 litre

Use: Normal

Intervals: Change 15000 km/ 12 months

Products:
TITAN SUPERSYN LONGLIFE SAE 5W-40 (year-round)
TITAN SUPERSYN SAE 5W-30 (year-round)
TITAN SUPERSYN SAE 5W-40 (year-round)
TITAN SUPERSYN SAE 5W-50 (year-round)
TITAN SYN MC SAE 10W-40 (Above -20°C)
TITAN FORMULA SAE 15W-40 (Above -15°C)
TITAN UNIMAX ULTRA MC SAE 10W-40 (Above -20°C)
TITAN UNIMAX PLUS MC SAE 10W-40 (Above -20°C)
TITAN UNIVERSAL HD SAE 15W-40 (Above -15°C)

Transaxle, automatic AF 17 4/1

Capacity: Capacity 4 litre

Use: Normal

Intervals: Check 24 months/ 30000 km

Products: **TITAN ATF 4000 (year-round)**

Transaxle, manual F17 5/1

Capacity:	Capacity 1,6 litre
Use:	Normal
Products:	TITAN SINTOFLUID SAE 75W-80 (year-round)

Hydraulic brake/clutch system

Use:	Normal
Intervals:	Check 15000 km/ 12 months Change 24 months
Products:	MAINTAIN DOT 514 LV (year-round) MAINTAIN DOT 5.1 (year-round) MAINTAIN DOT 4 LV (year-round) MAINTAIN DOT 4 HT (year-round) MAINTAIN DOT 4 (year-round)

Power steering

Use:	Normal
Intervals:	Check 24 months/ 30000 km
Products:	TITAN CHF 202 (year-round)

Cooling system

Capacity:	Capacity 6,4-6,8 litre
Use:	Normal
Intervals:	Check 15000 km/ 12 months
Products:	MAINTAIN FRICOFIN LL (year-round) MAINTAIN FRICOFIN LL 50 (Ready-Mix) (year-round)

The information contained in the oil chooser is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in the oil chooser represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all information given in the oil chooser at any time and without warning, unless otherwise provided in customer-specific agreements. With this publication, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH. © FUCHS SCHMIERSTOFFE GMBH. All rights reserved.